



Suitable for  
solar operation

## COOLMATIC CDF-45

<b>Gross capacity:</b>	39 litres
<b>Voltage:</b>	12/24 volts DC
<b>Average power consumption:</b>	45 watts
<b>Average running time:</b>	25% at 20°C ambient temperature, 35% at 30°C ambient temperature, both at 5°C interior temperature
<b>Power consumption:</b>	power input x average running time
<b>Temperature range:</b>	10°C to >= -15° C, variable via electronic thermostat
<b>System:</b>	fully hermetic Danfoss BD35F compressor with integrated control electronics, low-voltage protection adjustable for consumer or starter battery by means of a slide switch, electronic fuse/automatic reverse pole protection, dynamically ventilated wire condenser, aluminium rollbond evaporator, heat dissipation to the outside by brushless, wear-free fan
<b>Material:</b>	cabinet: PP, lid: PE
<b>Colour:</b>	cabinet: pale grey, lid: dark grey
<b>Weight:</b>	19 kg
<b>Quality features:</b>	detachable lid (hinge at the front), vertical space for standing 2.0-litre bottles
<b>Scope of delivery:</b>	DC connection cable
<b>Test mark:</b>	e-approved according to 95/54/EC (EMC guideline for vehicles), TÜV Rheinland, GS
<b>Optional extras:</b>	High quality insulating protective cover <b>Universal fixing kit</b>
<b>Product Ref:</b>	CDF-045DC